

Version: ROW

Country of Origin: Made in China

Last update: 03.11.2025

## TECHNICAL SPECIFICATIONS

<b>Product type</b>	SPC (Rigid LVT)	<b>Installation</b>	Floating (Angle-Angle)
<b>Overall thickness</b>	5.0 mm	<b>Bevel</b>	Cut bevel on 4 sides
<b>Wear layer</b>	0.5 mm	<b>Backing type and thickness</b>	1 mm IXPE
<b>Finish</b>	Anti-microbial PureCoat UV coating		

## CLASS OF USE AND WARRANTY

<b>Domestic</b>	23 Heavy	<b>Commercial</b>	31 Moderate
<b>Domestic Warranty</b>	Lifetime Limited	<b>Commercial Warranty</b>	15 Years Limited

## ENVIRONMENTAL IMPACT

<b>Life Cycle Assessment</b>	Oct 2022	<b>Environmental Product Declaration</b>	Oct 2022 - Oct 2027
------------------------------	----------	------------------------------------------	---------------------

## CERTIFICATIONS

<b>CE Marking</b>	Certified	<b>GreenGuard Gold</b>	Certified
<b>UKCA Marking</b>	Certified	<b>Product Health Declaration</b>	HPDC
<b>IAC Gold</b>	Certified	<b>Assure</b>	Certified

## CHEMICAL PROPERTIES

Norm	Item	Test Method	Requirement	Result
EN 14041	Emissions	EN 717-1	≤0.12 mg/m <sup>3</sup>	Compliant
Decret No.2011-321	Emissions	ISO 16000	VOC A+ (TVOC<1000 µg/m <sup>3</sup> )	Compliant
CDPH	Emissions	Spectrometry, chromatography	TVOC ≤220 µg/m <sup>3</sup>	Compliant
CPSIA & Prop 65	Ortho-Phthalates	CPSC-CH-C-1001-09.4	N.D.	Compliant
REACH	SVHC	Spectrometry, chromatography	≤0.1 %	Compliant

## PHYSICAL PROPERTIES

Norm	Item	Test Method	Requirement	Result
ISO 10582	Length	ISO 24342	≤0.15 % of nominal length up to max 0.5 mm	Compliant
	Width	ISO 24342	≤0.1 % of nominal width up to max 0.5 mm	Compliant
	Squareness and straightness	ISO 24342	≤0.25 mm/≤400 mm ≤0.35 mm/≥400 mm	Compliant
	Total thickness (with backing)	ISO 24346	+0.13 mm/-0.1 mm, max ±0.15 mm	Compliant
	Wear layer thickness	ISO 24340	+13 %, -10 %	Compliant
	Dimensional stability (6hrs at 80°C)	ISO 23999	ΔW/ΔL ≤0.15 %	Compliant
	Curling	ISO 23999	≤1 mm	Compliant
	Castor chair	ISO 4918	Moderate Commercial 15,000 R	Compliant
	Residual indentation	ISO 24343-1	≤0.1 mm	Compliant
	Light fatness (blue wool)	ISO 105-B02:2014 Method 3A	≥Grade 6	Compliant
	Flatness	ISO 10582 Appendix B	Length: ≤0.50 % (concave) / ≤1.0 % (convex) Width: ≤0.10 % (concave) / ≤0.15 % (convex)	Compliant
	Openings	ISO 10582 Appendix C	Average ≤0.15 mm / Max ≤0.2 mm	Compliant
	Height difference	ISO 10582 Appendix C	Average ≤0.1 mm / Max ≤0.15 mm	Compliant
	Locking strength	ISO 10582 Appendix D	≥1.5 KN/m	Compliant
EN 16511	Wear resistance	EN 13329 /ISO 24338 Procedure A	≥4000 cycles (AC4)	Compliant
	Impact resistance	EN 13329 Annex F	≥1600 mm	Compliant
	Martindale (gloss retention)	EN 16094	≤MSR-A2	Compliant
	Martindale (micro-scratch)	EN 16094	≤MSR-B2	Compliant

	Furniture leg	EN ISO 16581	No visible damage	Compliant
	Resistance to staining	EN 438-2	Group 1 and 2: Grade 5 Group 3: Grade 4	Compliant
EN 14041	Swelling	ISO 24336	≤12 %	Compliant
	Thermal Resistance (R)	EN 12664/ASTM C518	NA	Compliant
	Slipperiness	EN 13893	≥0.3	Compliant
	Reaction to fire	EN 13501-1	Class Bfl -s1	Compliant
OTHERS	Slipperiness	DIN 51130 /DIN EN 16165 Annex B	≥R9	Compliant
	Airborne sound transmission	ISO 10140-2	N/A	67 dB*
	Impact sound transmission	ISO 10140-3	N/A	42 dB*
	Impact sound transmission - Reduction	ISO 10140-1	N/A	18 dB*

\*Acoustic performance results are provided for reference only.

## LEED SCORECARD

How our products fit into LEED v4:

	Credit Type	Points	Criteria	Product Contribution
LEED BD+C and ID+C	EQ Credit: Low-Emitting Materials	1-3 points	Option 1. Product has been tested according to California Department of Public Health (CDPH) Standard Method v1.2-2017 and complies with the VOC limits in Table 4-1 of the method. Additionally, the range of total VOCs after 14 days (336 hours) was measured as specified in the CDPH Standard Method v1.2 and is reported (TVOC ranges: 0.5 mg/m3 or less, between 0.5 and 5 mg/m3, or 5 mg/m3 or more).	CFL Rigid Core products are GreenGuard Gold and/or FloorScore certified.
			Option 2. Product has been tested according to EN 16516:2017 and complies with the LCI values from Table 1 of the German AgBB Testing and Evaluation Scheme (2015) and a formaldehyde limit of 10 micrograms per cubic meter. Additionally, the range of total VOCs after 28 days was measured as specified in EN 16516 and reported (TVOC ranges: 0.5 mg/m3 or less, between 0.5 and 5 mg/m3, or 5 mg/m3 or more).	CFL Rigid Core products are IAC Gold certified, including compliance with German AgBB testing.
		MR Credit: Building Product Disclosure and Optimization – Environmental Product Declarations	1 point	Option 1. Environmental Product Declaration (EPD) Environmental Product Declarations which conform to ISO 14025 and EN 15804 or ISO 21930 and have at least a cradle to gate scope. Product-specific Type III EPD – Products with third-party certification (Type III), including external verification and external critical review are valued as 1.5 products for the purposes of credit achievement calculation.
	MR Credit: Building Product Disclosure and Optimization – Material Ingredients	1 point	Option 1. Material Ingredient Reporting Health Product Declaration. The end use product has a published and complete Health Product Declaration with full disclosure of known hazards in compliance with the Health Product Declaration open Standard.  Option 2: Material Ingredient Optimization International Alternative Compliance Path – REACH Optimization (value at 100% of cost or 1 product). End use products and materials have fully inventoried chemical ingredients to 100 ppm and assess each substance against the Authorization List – Annex XIV, the Restriction list – Annex XVII and the SVHC candidate list, (the version in effect June 2013,) proving that no such substance is included in the product. If the product contains no ingredients listed on the REACH Authorization, Restriction, and Candidate list.	CFL SPC (Made in China) Health Product Declaration - HPDC Builder  CFL products are REACH compliant.

## WELL SCORECARD

The WELL Building Standard is founded on the understanding that facets of our environment interact with personal, genetic and behavioral factors to shape our overall health and well-being. By compiling leading practices in building design and management and referencing existing standards and best practice guidelines set by governmental and professional organizations, WELL works to harmonize and clarify existing thresholds and requirements.

Facet	Feature	Part	Requirements	Concept score	How our product contribute to obtain WELL level certification
AIR	01. Air quality standards	1. Standards For Volatile Substances	The following conditions are met:	PRECONDITION	a. Formaldehyde emission are less than 27 ppb.  b. The total volatile organic compounds are less than 0.5 mg/m3.
			a. Formaldehyde levels less than 27 ppb (0.027 ppm)  b. Total volatile organic compounds less than 500 ug/m3 (0.5 mg/m3)		

04. VOC Reduction	1. Interior Paints and Coatings	The VOC limits of newly applied paints and coating meet one of the following requirements:  a. 100 % of installed products meet California Air Resources Board (CARB) 2007, Suggested Control Measure (SCM) for Architectural Coatings, or South Coast Air Quality Management District (SCAQMD) Rule 1113, effective June 3, 2011 for VOC content.  b. At minimum 90 %, by volume, meet the California Department of Public Health (CDPH) Standard Method v1.1-2010 for VOC emissions	PRECONDITION	a. The VOC limits for California Air Resources Board (CARB) are less than 0.11 ppm.  b. Measured Concentration of Total Volatile Organic Compounds (TVOC): Less than/equal to 0.5 mg/m <sup>3</sup> (in compliance with CDPH/EHLB Standard Method v1.1-2010).  The product is GreenGuard Gold certified
	3. Flooring	The VOC emissions of all newly installed flooring must meet all limits set by the following, as applicable:  a. California Department of Public Health (CDPH) Standard Method v1.1-2010.	PRECONDITION	Conforms to the CDPH/EHLB Standard Method v1.1-2010 (California Section 01350), effective January 1, 2012, for the school classroom and private office parameters when modeled as Flooring.  The product is GreenGuard Gold certified
11. Fundamental Material Safety	1. Asbestos and Lead Restriction	All newly-installed building materials meet the following materials composition requirements: a. No asbestos. b. Not more than 100 ppm (by weight) added lead.	PRECONDITION	a. No asbestos b. The product contain less than 100 ppm.
	2. Lead Abatement	For repair, renovation or painting on buildings constructed prior to any applicable laws banning or restricting lead paint, lead evaluation and abatement.	PRECONDITION	The product contain less than 90 ppm.
	3. Asbestos Abatement	To reduce hazards in buildings constructed prior to any applicable laws banning or restricting asbestos, the following testing, evaluation and abatement.	PRECONDITION	The product contain less than 90 ppm.
25. Toxic Material Reduction	2. Flame Retardant Limitation	Halogenated flame retardants are limited in the following components to 0.01 % (100 ppm) to the extent allowable by local code: a. Window and waterproofing membranes, door and window frames and siding. b. Flooring, ceiling tiles and wall coverings. c. Piping and electrical cables, conduits and junction boxes. d. Sound and thermal insulation. e. Upholstered furniture and furnishings, textiles and fabrics.	OPTIMIZATION	The product don't contain halogenated flame retardants
	3. Phthalate (Plasticizers) Limitation	DEHP, DBP, BBP, DINP, DIDP or DNOP (often found in polyvinyl chloride [PVC]) are limited in the following components to 0.01 % (100 ppm): a. Flooring, including resilient and hard surface flooring and carpet. b. Wall coverings, window blinds and shades, shower curtains, furniture and upholstery. c. Plumbing pipes and moisture barriers.	OPTIMIZATION	In accordance with US Consumer Product Safety Improvement Act 2008 (CPSIA) (H.R.4040) Title I, Section 108 & California Proposition 65 & Annex XV II item 51&52 of the REACH Regulation (EC) No. 1907/2006 and amendment No. 552/2009, the product contains less than 100ppm.
	5. Urea-Formaldehyde Restriction	Urea-formaldehyde presence is limited in the following components to 100 ppm: a. Furniture or any composite wood products. b. Laminating adhesives and resins. c. Thermal insulation.	OPTIMIZATION	The product contains urea-formaldehyde less than 100 ppm.

**Comfort****74. Exterior Noise Intrusion****Part 1. Sound Pressure Level**

Each regularly occupied space meets the following sound pressure level as measured when the space and adjacent spaces are unoccupied, but within 1 hour of normal business hours:

- a. Average sound pressure level from outside noise intrusion does not exceed 50 dBA.

**PRECONDITION**

1. The product has  $L_{nw} = 42$  dB according to the standard ISO 10140-3
2. The product has  $R_w = 67$  dB according to the standard ISO 10140-2

**79. Internally Generated Noise****Part 1. Sound Masking Limits**

If sound masking systems are used, sound levels fall within the following range, when measured from the nearest workspace:

- a. Open workspaces: 45 - 48 dBA.
- b. Enclosed offices: 40 - 42 dBA

**OPTIMIZATION**

1. The product has  $L_{nw} = 42$  dB according to the standard ISO 10140-3
2. The product has  $R_w = 67$  dB according to the standard ISO 10140-2

---

**END OF DOCUMENT**