

Basetec (63002990)

Version: 07/03/2022

Product description

Underlay for click vinyl planks and tiles.

- Reduces noise and works as an isolation layer.
- Corrects minor imperfections in the subfloor.
- Can function as a vapour barrier when properly installed.

Suitable for underfloor heating.


Logistic information

	contains	length	width	thickness	weight
		8500 mm	1180 mm	1 mm	1.3 kg
1 box		1200 mm	270 mm	45 mm	1.8 kg
1 pallet	45 boxes	1200 mm	800 mm	835 mm	106 kg

Installation

Unfold the underlay and flatten it. Slice with a standard cutter knife. Connect the different layers with aluminium tape to create a vapour barrier.





Product composition


Pressure-resistant non woven foam with antislip surface and integrated water vapour layer.

Storage


Do not store outdoors, protect from exposure to sunlight. Prevent electrostatic discharges: keep away from ignition sources and avoid smoking nearby.

Requirements


Characteristics	Method	Value
Thickness of the underlay measured	EN 823	1 mm
Foam colour		black
Impact sound reduction	ISO 10140	16 dB
Compressive strength	EN 826	≥ 400 kPa
Punctual conformability	ISO 868 / TS 16354	≥ 0,5 mm
Thermal resistance	DIN 4108	0.03 m ² K/W
Water absorption	EN 12087	≤ 1 %
Dynamic load resistance	EN 13793 / TS 16354	≥ 250.000 cycles




impact sound
-16 dB




suitable for
floor heating



corrects un-
evenness &
protects loc
system



integrated
moisture
barrier



protects
against loads



ÉMISSIONS DANS L'AIR INTÉRIEUR*
A+

*Informations sur le niveau d'émission de substances volatiles dans l'air intérieur, présentant un risque de toxicité par inhalation, sur une échelle de classe allant de A+ (pas de risque d'émission) à C (forte émission).