

Art. no.: 313.05

OX-ON Mask FFP1 NR D w/ Valve Comfort



Features:

- Suitable for work in dusty environments
- Valve prevents accumulation of moisture and heat
- Extremely low breathing resistance
- Aluminium nose bridge
- Latex-free elastic band
- 10 pcs. masks per box.

Colours:

white

Total CO2 emission:

0.099 Kg CO2 eq.

Materials:

Total water consumption:
0.013 m3 world eq.

Product Description:

OX-ON Mask FFP1NR D w/Valve Comfort is the safety approved filtrating single-use mask with valve, which you can use when working with less hazardous dry particles and liquid aerosols with a Workplace Exposure Limit (WEL) <5 mg/m3 (max. concentration 4 x WEL).

Among other things, you can use the disposable mask when you work within the industry or in agriculture and forestry. For example, you can use the mask when working with cardboard, textiles, feathers, graphite, clay, pollen, grinding of aluminium, plaster and quartz-free stone.

The mask is dolomite tested, which means that you get a filter with a particularly large dust capacity with slowly increasing resistance. At the same time, this quality mask is provided with a valve, which ensures you great comfort and a pleasant climate in the mask when you use it. The valve helps to prevent the accumulation of moisture and heat when wearing it.

The sealing soft foam rubber at the nose as well as the mouldable aluminium nose bridge ensure you a perfect and comfortable adaptation to your face. The elastic band of the mask is latex-free.

You get 10 pcs. masks per box.

Sizes:

| STR. | ART. NO. | EAN |
|----------|----------|---------------|
| One size | 313.05 | 5701952313051 |

Minimum sales and packaging:

| MINIMUM ORDER | PK. | KLL. |
|---------------|-----|---------|
| 1 æske | N/A | 12 æske |

| | |
|--------------|--|
| EN standards | EN 149 |
| Certificates | CAT. III |
| Features | ADJUSTABLE NOSE-CLIP MASKE WITH VALVE |