

Floorstanding WC combination with cistern  
with fixing holes for floor fixation  
82736.2



TECHNICAL DATA

Order no.	82736.2
Certified to	EN 997
Specification	Washdown for 4,5/3-l-flush, Charge 782 4 fixing holes with cistern flushing mechanism, water condensation insulation, Dual-Flush (4,5/3-l-flush), water inlet bottom right 1/2" brass
Outlet	horizontal VARIO, vertical 70 - 200 mm
Weight	32,0 kg
Accessories incl.	2x fastening kit, order no. 89128.2
Accessories excl.	Seat and cover, order no. 89336.0 Seat and cover with automatic lowering system, order no. 89336.1

Mounting acc. excl.	for VARIO-outlet 70 - 160 mm LAUFEN- connection, order no. 89009.2 for VARIO-outlet 160 - 200 mm only LAUFEN- connection, order no. 89902.5
---------------------	--

Colours	see colour table
---------	------------------

SPECIFICATION TEXT

Floorstanding WC pan washdown Laufen-RIGO, sanitary ceramic, with cistern Dual-Flush (4,5/3-l-flush)  
EN 997, 4,5/3-l-flush, dimensions 360 x 650 x 850 mm  
outlet horizontal, VARIO vertical 70 - 200 mm  
back to wall, 4 fixing holes  
Special feature: concealed surfaces directing water are fully glazed throughout, vacuum checked  
Further options / accessories: WC seat and cover 89336.0,  
WC seat and cover with automatic lowering system 89336.1  
Order no. 82736.2

TECHNICAL DRAWINGS / S 1 : 20

