



**Digital residual current circuit-breaker/miniature circuit-breaker,  
25A, 30mA, miniature circuit-breaker trip curve: C, 2 p, residual current  
circuit-breaker trip characteristic: G/A**

**Part no. dRBM-25/2/C/003-G/A**  
**Article no. 168326**  
**Catalog No. PDC-TBD6441**

Similar to illustration

## Technical data ETIM 6.0

Circuit breakers and fuses (EG000020) / Earth leakage circuit breaker (EC000905)

Electric engineering, automation, process control engineering / Electrical installation, device / Residual current protection system / MCB/RCCB combination (ecl@ss8.1-27-14-22-07 [AFZ810012])

|   |  |    |       |
|---|--|----|-------|
| Number of poles (total)                           |  |    | 2     |
| Number of protected poles                         |  |    | 2     |
| Nominal rated voltage                             |  | V  | 240   |
| Nominal rated current                             |  | A  | 25    |
| Rated fault current                               |  | A  | 0.03  |
| Leakage current type                              |  |    | A     |
| Current limiting class                            |  |    | 3     |
| Rated short-circuit breaking capacity EN 60898    |  | kA | 10    |
| Rated short-circuit breaking capacity IEC 60947-2 |  | kA | 0     |
| Frequency   |  |    | 50 Hz |
| Release characteristic                            |  |    | C     |
| Concurrently switching N-neutral                  |  |    | No    |
| Over voltage category                             |  |    | 3     |
| Pollution degree                                  |  |    | 2     |
| Width in number of modular spacings               |  |    | 2     |
| Built-in depth                                    |  | mm | 75    |
| Degree of protection (IP)                         |  |    | IP20  |