

## Technical data sheet

domestic Extra  
Version 09.2013

### Dimensions

Tongue and groove	Perfect Fold 3.0 connection
Format	Classic Plank
Bevels	none
Thickness	8mm
Width	190mm
Length	1200mm
Number of panels per pack	7
m <sup>2</sup> per pack	1,596m <sup>2</sup>
Heat resistance	0,06m <sup>2</sup> K/W

### Factory warranty

	Method	Parameters	Norm requirements	Pergo values
Usage class	EN 13329			21-22-23/31-32
CE	EN 14041	Notified body	0380-1161	DOP PL0501
Warranty	Residential use	warranty conditions in each pack		20 years
	Commercial use			3 years

### General data

	Method	Parameters	Norm requirements	Pergo values
Wear resistance	EN 13329		≥ 4000	≥ 4000
Wear class	EN 13329		AC4	AC4
Impact resistance	EN 13329		IC2	IC2
Scratch resistance	EN 438-2, 25		Charge ≥ 3.0 N	Charge ≥ 5 N
Slip resistance	EN13893			DS
Emission formaldehyde	EN 717			E1 <0,020 ppm
Fire classification	EN 14041			Cfl - s1
Moisture swelling	EN 13329	after 24h immersion at 20°C	≤18%	≤ 15%
Castor chairs	EN 13329	Type W(EN 12529)	25000 cycles	No change



## Technical data sheet

domestic Extra  
Version 09.2013

### General data

	Method	Parameters	Norm requirements	Pergo values
General appearance	EN 13329	Height differences	≤ 0,15 mm	≤ 0,10 mm
		Opening between joints	≤ 0,20 mm	≤ 0,10 mm
		Cupping in the length	cc ≤ 0,50%    cv ≤ 1,00%	cc ≤ 0,50%    cv ≤ 1,00%
		Cupping in the width	cc ≤ 0,15%    cv ≤ 0,20%	cc ≤ 0,15%    cv ≤ 0,20%
Light fastness	EN 13329	Blue reference	Class 6	Class > 6
Burning cigarette	EN 438-2, 30	Class 4		Class 5
Resistance against staining	EN 13329	Group 1,2	Class 5	Class 5
		Group 3	Class 4	Class 5
		Group 4	-	Class 4
Displacement of furniture feet	EN 424	Foot 0,1 mm / 32 kg		No change
		Foot 3 mm / 100 kg		No change
		Foot 2 mm / 100 kg		No change
Dimensional variations	ISO 24339	Variation in length AND width		≤ 0,10%
Anti-static	EN 14041	Charge human body at 25% RH and 23°C		≤ 2,0kV
Floor heating	On a Pergo underlay	See special instructions		Suitable

### Ecological certificates

U-sign	Request pending
AFFSET	A+
Nordic ecolabel	329 001
PEFC	PEFC/07-32-37
M1	Request pending

Note: For all characteristics of the surface layer, a zone of 5mm along the V-groove is excluded

